



flooring for life.

# MAINTENANCE

## OILED FLOOR CARE ROUTINE

### PREVENTION

Install barrier mats such as coir matting inside and outside all external doorways. Wipe up any spilled liquids with a wet damp cloth as wood will absorb liquid and expand which could affect the stability of the floor. Avoid use of any household cleaners. These can be aggressive and damage or dull the surface and can leave a dangerous slippery film. Your wood needs the right environment: ideally, a room temperature between 15 and 24 degrees Celsius and around 40-65% relative air humidity. Stick felt pads under the legs of all furniture. Lift and avoid dragging when moving the furniture.

### REGULAR DRY CLEANING

To prevent any hard particles from building up on your flooring, regularly dust your floors with a non-abrasive, lint-free mop. Microfibre mops like the **Vileda Spray Pro Inox Mop Kit** are great for both dry and wet cleaning of your floors and will help you maintain the look of the high sheen levels.



### REGULAR DAMP CLEANING

For regular damp cleaning we recommend **Eco Wash Care**, an environmentally friendly, PH neutral floor cleaning system designed for everyday cleaning of oiled and lacquered wooden floors. Paired with a **Vileda Spray Pro Inox Mop Kit** you can be assured your flooring will be gently and thoroughly cleaned and dirt repellent.



### CARE & REGENERATION

Reviving your oiled flooring is quite simple when using our **Wax Care**. This solution will regenerate and freshen up worn oak floor surfaces while simultaneously improving wear protection. To use, apply **Wax Care** on dust-cleaned floor and rub evenly with a cloth – let dry and polish with a cloth or . Be sure to use this do this approx. every 3 months or as required - in very high traffic areas this could be required monthly or even weekly. In larger areas this can be applied via a slowly rotating buffing machine.



### INTENSIVE CLEANING

**Eco Magic Cleaner** is recommend for intensive cleaning of heavily worn oak floor surfaces. For removal of surface stains & worn bare oak, put a small quantity of **Eco Magic Cleaner** on your floor and leave for 5-10 minutes then wash off with clean water. Be careful that you do not use steel wool, micro fibre or abrasive cleaner when using **Eco Magic Cleaner**. After using magic cleaner a protective coat should be applied. We recommend maintenance oil or hard wax oil, depending on wear.



### RESTORATION

**Maintenance Oil** is recommended for infrequent maintenance of heavily used wood flooring. Clean the surfaces to be treated with **Eco Magic Cleaner** prior to application. On the clean floor, spread and rub in the oil evenly with a cloth and let dry. For removal of stubborn stains: pour small quantity of **Maintenance Oil** on the floor and rub the stain with a rag. Never use steel wool, filament mop (microfibre) or abrasive cleaners!



© This information sheet was compiled and written by Chaunceys Timber Flooring at 9 Victoria Road, St Phillips, Bristol, BS2 0UJ. At the time of compiling this information sheet, we believe our recommendations to be wholly accurate, however, they are non-binding recommendations. Since the application and processing of the products is beyond our control, the responsibility rests solely with the user. When a new info sheet on this topic is published the previous version loses its validity. The photographs in this sheet are intended only as illustrations.